



CTEK PRO 25SE

25A Workshop Charging

Part No: 15000520



Designed for busy workshops, PRO 25SE has high end features built into a small, portable package.

Simple, yet Powerful

Commencing charging has never been simpler! Set the desired mode using the 'MODE' button and let the charger do the rest!

Fitted with CTEK's 8 step charging technology, PRO 25SE will de-sulphate the battery, check it can receive and hold a charge and when charging has completed, PRO 25SE will go into a float mode allowing you to leave the battery for as long as you like and it will remain at 100% charge.

Diagnostics and Maintenance

Need to perform an ECU update or carry out any other diagnostic works? When put into SUPPLY mode PRO 25SE can provide a constant 25A/12V supply. Automatic parallel load compensation ensures that the voltage stays constant throughout.

Quick Overview

- ✓ CTEK 8 Step Charging
- ✓ 25A SUPPLY Mode
- ✓ Simple One Button Operation
- ✓ Lithium Compatible
- ✓ Temperature Compensation
- ✓ 6 Metre Charge Cables
- ✓ RECOND Mode

Made for workshops

Designed to be your go to workshop battery charger and maintainer, PRO 25SE is encased in a lightweight yet durable IP44 protected enclosure allowing you take PRO 25SE where you need it.

PRO 25SE can be mounted to a wall using the optional wall bracket or it can be mounted on CTEK's Trolley Pro for effortless workshop transportation.

RECOND Mode

Designed for use with deeply discharged wet Lead-Acid batteries to bring them back to life! Simply select RECOND mode and the charger will go through the same charging process as normal except at stage 6 it will raise the voltage in a controlled way to prevent acid stratification and prolong battery life.

CTEK 8 Step Charging

Lithium Mode

One Button Operation

Included Wall Mount

Temperature Sensor

Supported 12V Batteries

Lead-Acid, AGM, GEL, EFB & LiFeP04

Safety Features

Spark free, reverse polarity and volt surge protected

Lithium Compatible

Maintain any 12V battery that enters your workshop. PRO 25SE can charge and maintain most Lead-Acid batteries including Flooded, AGM, EFB and GEL. There is a dedicated Lithium mode for charging lithium batteries including LiFeP04.

Battery Diagnostics

To help safely and efficiently charge batteries PRO 25SE uses advanced technologies to detect how the battery is performing whilst charging. A Temperature sensor sits along side the clamps that continuously monitors temperature and parallel load compensation ensures that when in SUPPLY mode a constant supply of 25A/12V power is supplied.

Error Detection

25A SUPPLY Mode

RECOND Mode

Durable Enclosure

6 Metre Cables



Cables

6 metre cables with durable clamps

Temperature Sensor

Automatic Temperature Compensation

Warranty

2 Years Manufacturer Warranty

Durable Design

IP44 protection from splashes and dust

Specifications

| | |
|--------------------------------|--|
| Supported Battery Types | Flooded Lead-Acid, AGM, EFB, GEL & Lithium |
| Power Output | 25A |
| Safety Features | Spark Free Reverse Polarity Protected Automatic Parallel Load Compensation |
| Power Supply Mode | Constant 25A Supply |
| Cables | 6 Metre |
| User Input | Simple One Button Design |
| Protection | IP44 |

Accessories



Wall Hanger

With built in cable storage



Trolley PRO

Effortless Workshop Transportation